



Volkswagen GTI SOHC 8v

Effective January 2021
Prices Subject To Change
Without Notice!

VALVE LIFT	DURATION	DURATION @ .050	GRIND NUMBER	DESCRIPTION	REGRIND	HARDWELD	BILLET
.598/.598	318°/318°	286°/286°	471	Special racing cam. Cam has a reduced base circle 1.240". Requires Larger Diameter Followers, and Shim Under Followers.	N/A	N/A	00-582 \$401.00
.550/.550	317°/317°	283°/283°	198	Tremendous top end performance. Cam has a reduced base circle 1.340". Requires Larger Diameter Followers, and Shim Under Followers.	N/A	N/A	00-282 \$401.00
.500/.500	301°/301°	275°/275°	206	Very strong upper and mid range power for carbureted racing engines. Cam has a reduced base circle 1.340". Requires Shim Under Followers.	N/A	N/A	00-352 \$401.00
.500/.500	301°/301°	281°/281°	230	Strong upper end performance for carbureted engines. Cam has a reduced base circle 1.340". Requires Larger Diameter Followers, and Shim Under Followers.	N/A	N/A	00-022 \$401.00
.480/.480	288°/288°	261°/261°	211	Designed for 1600cc off-road racers. Very broad power range. Cam has a reduced base circle 1.340". Requires Shim Under Followers.	N/A	N/A	00-342 \$401.00
.480/.480	292°/292°	266°/266°	136	Strong mid and upper end performance for racing engines. Cam has a reduced base circle 1.340". Requires Shim Under Followers.	N/A	N/A	00-272 \$401.00
.477/.477	283°/283°	257°/257°	221	High lift short duration cam produces good overall power. Cam has a reduced base circle 1.340". Requires Shim Under Followers.	N/A	N/A	00-402 \$401.00



Volkswagen GTI SOHC 8v

Effective January 2021
Prices Subject To Change
Without Notice!

VALVE LIFT	DURATION	DURATION @ .050	GRIND NUMBER	DESCRIPTION	REGRIND	HARDWELD	BILLET
.460/.460	290°/290°	262°/262°	122	Consistent winner for 1600cc desert racers. Cam has a reduced base circle 1.340".	N/A	N/A	00-332 \$401.00
.450/.450	280°/280°	247°/247°	253	Very broad power range for hot street and off-road engines. Cam has a reduced base circle 1.340".	N/A	N/A	00-732 \$401.00
.450/.450	280°/280°	247°/247°	253	Very broad power range for hot street and off-road engines. Cam has a stock base circle 1.500".	N/A	N/A	00-412 \$401.00
.442/.442	239°/239°	222°/222°	279	Hydraulic profile offers improved overall power for late model fuel injected cars. Stock base circle.	N/A	N/A	00-162 \$401.00
.441/.441	244°/244°	227°/227°	278	Hydraulic profile offers improved upper end power over grind 279. Fair idle. Stock base circle.	N/A	N/A	00-492 \$401.00
.435/.435	288°/288°	260°/260°	125	Strong mid and upper end performance for hot street. Use with carburetors. Stock base circle.	N/A	N/A	00-322 \$401.00
.433/.433	272°/272°	238°/238°	111	Broad power range for high performance street engines. For fuel-injected engines. Fits mechanical engines.	N/A	N/A	00-172 \$401.00



Volkswagen GTI SOHC 8v

Effective January 2021
Prices Subject To Change
Without Notice!

VALVE LIFT	DURATION	DURATION @ .050	GRIND NUMBER	DESCRIPTION	REGRIND	HARDWELD	BILLET
.433/.433	272°/272°	238°/238°	111	Broad power range for high performance street engines. For carbureted engines. Fits mechanical engines.	N/A	N/A	00-132 \$401.00
.430/.430	255°/255°	237°/237°	268	Hydraulic profile offers improved upper end performance. Stock base circle.	N/A	N/A	00-702 \$401.00
.428/.428	243°/243°	225°/225°	269	Bolt in profile for mechanical engines. Specify for fuel injection or carbureted.	N/A	N/A	00-652 \$401.00
.423/.423	278°/278°	250°/250°	1039	Performance profile designed for mechanical engines for the SCCA Class Spec Rules.	N/A	N/A	00-772 \$401.00
	0°/0°	0°/0°	Stock	New cam, or grind yours to factory specifications.	00-200 \$151.00	N/A	00-202 \$401.00
Buckets, Shim Under (Kroyer) Pro, Specially Coated WCC Oversized				Custom sizes, shim under-style. Price (Each).			CF-V00 \$70.00
Valve Springs Only Racing				Performance dual valve springs. Does not fit cross flow head. OK to 0.500" valve lift. OK to use stock retainers. Price Per Set (8).			VS-R16 \$92.80